



product description: intended for installation to the distribution of low voltage
 standard shape
 designed for wall or ceiling mounting
 possibility to install in places with risk of flammable gases and vapor – danger zone 2
 possibility to install in places with explosive risk of dust – danger zone 22

material: PVC - Pb-free
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 flaming loop test: 850 °C
 impact strength: 0,5 J
 protection types: IP40
 fire class for underlying material: A1-F
 inside area: 50 mm²
 distance base perforation: 200 ±20 mm
 length tolerance: ±10 mm
 weight: 0,07 kg/m
 certification: EN 50085-1 ed.2:06, EN 50085-2-1:07
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

item number	length	color	package	package - description	note
LV 11X10_HD	2 m	white RAL 9003	150 m	carton	-
LV 11X10_P2	2 m	white RAL 9003	150 m	carton	self-adhesive tape