



typové číslo	length L (mm)	width A (mm)	min. wrap diameter (mm)	max. wrap diameter (mm)	opening force (N)	package (pcs)	color
<b>SP 100X2.5_FA</b>	100	2,5	3	20	80	100	black
<b>SP 100X2.5_HA</b>	100	2,5	3	20	80	100	natural
<b>SP 140X3.5_HA</b>	150	3,6	3	33	180	100	natural
<b>SP 140X3.5_FA</b>	150	3,6	3	33	180	100	black
<b>SP 140X4.5_HA</b>	140	4,5	4	36	280	100	natural
<b>SP 160X2.5_HA</b>	165	2,5	4	39	80	100	natural
<b>SP 160X4.5_HA</b>	160	4,8	5	35	220	100	natural
<b>SP 180X4.5_FA</b>	190	4,8	4	45	220	100	black
<b>SP 180X4.5_HA</b>	190	4,8	4	45	220	100	natural
<b>SP 200X4.5_FA</b>	190	4,8	4	45	220	100	black
<b>SP 200X4.5_HA</b>	190	4,8	4	45	220	100	natural
<b>SP 250X4.5_HA</b>	250	4,8	5	62	220	100	natural
<b>SP 280X4.5_FA</b>	310	4,8	7	79	220	100	black
<b>SP 280X4.5_HA</b>	310	4,8	7	79	220	100	natural
<b>SP 360X4.5_FA</b>	368	4,8	7	96	220	100	black
<b>SP 360X4.5_HA</b>	368	4,8	7	96	220	100	natural
<b>SP 360X7.5_FA</b>	380	7,6	8	96	550	100	black
<b>SP 360X7.5_HA</b>	380	7,6	8	96	550	100	natural
<b>SP 380X4.5_FA</b>	368	4,8	7	96	220	100	black
<b>SP 380X4.5_HA</b>	368	4,8	7	96	220	100	natural
<b>SP 430X4.5_FA</b>	450	4,8	8	129	220	100	black
<b>SP 430X4.5_HA</b>	450	4,8	8	129	220	100	natural

material: polyamide

halogen-free: yes

temperature resistance: -40 - +85 °C

temperature resistance for montage: -10 - +30 °C

storage: ČSN 64 0090

product description: for normal bundling and fixing of cables, wires and pipes  
 for fixing to a pad, use cable tie clamps SPPN 19X19 or SPP 19X19  
 fire resistance according to U.L. 94 - V2  
 not long-term resistant to sunlight

Recommendation: cable ties should be installed immediately after unpacking from the sealed bag. This will prevent unnecessary reduction in the level of humidity PA, which would result in a reduction of the cable tie quality.