TuffMaster Metal clad and ingress protected switches, sockets and RCDs

Ε

A range of IP (ingress protection) rated sockets and metal clad wiring accessories for demanding environments. The range covers installation at commercial, industrial, agricultural and outdoor domestic locations.



fMaster

The TuffMaster IP56 range is protected against adverse weather conditions when in use and fully closed. The range is designed to perform in demanding environments where exposure to dust or water may be encountered.

IP56 rating:



Product information

- **RCD** protected sockets
- Protected in use to IP56 when lid is fully closed
- 1 and 2 gang options available
- In case of earth leakage from a fault or accident, the RCD will automatically cut off power before injury or damage is caused

IP56 sockets

- · Protected in use to IP56 when lid is fully closed
- 1, 2 and 3 gang options
- International versions available

RCD switch socket combinations

Weatherproof to IP56

• Mechanically (passive) or electrically (active) latched

Standard colour LG LG: Light Grey

Options: Other colours are available but may be subject to lead times and minimum order quantities. White WH; Terracotta TC; Green GN; Grey dark GD; Orange OR.





1 gang 13Amp socket

size

TM5613LG 109 x 75 x 90mm

pack

code

code



2 gang 13Amp socket

size

TM5614LG 109 x 152 x 90mm 1

pack







pack

16Amp 230V socket outlet

onal)	
description/size	pack
Schuko outlet	1
109 x 75 x 90mm	
7LG French/Belgian outlet	
109 x 75 x 90mm	
	description/size Schuko outlet 109 x 75 x 90mm French/Belgian ou



 13Amp switched socket

 code
 description/size
 pack

 TM5618LG
 1 gang
 1

 109 x 152 x 90mm
 1

 TM5619LG
 2 gang
 1

 109 x 229 x 90mm
 1



 13Amp switched socket

 with neon

 code
 description/size pack

 TM5621LG
 1 gang double pole
 1

109 x 152 x 90mm



 IoAmp switched Schuko

 socket (international)

 code
 description/size

 TM5620LG
 2 gang
 1

 109 x 229 x 90mm
 1



 16Amp switched Schuko

 socket with neon

 (international)

 code
 description/size

 pack

 TM5622LG
 1 gang double pole
 1

 109 x 152 x 90mm





Fused spurswitched unit with neoncodesizepackTM5623LG109 x 152 x 90mm1

 Fused spur

 unswitched unit

 code
 size
 pack

 TM5624LG
 109 x 75 x 90mm
 1

Product information IP56 Empty enclosures

- · Protected in use to IP56 when lid is fully closed
- Available in 1, 2 and 3 gang versions
- Manufactured from polycarbonate



IP56 Empty Enclosures

code	description/size	pack
TM5628LG	Single grid 109 x 75 x 90mm	1
TM5629LG	Single grid lockable 109 x 75 x90mm	1
TM5630LG	Double grid 109 x 152 x 90mm	1
TM5631LG	Double grid lockable 109 x 152 x 90m	m 1
TM5632LG	Triple grid 109 x 229 x 90mm	1
TM5633LG	Triple grid lockable 109 x 229 x 90mm	1
TM5634BK	Single grid 109 x 75 x 90mm	1

Product information IP56 Lid/housing/RCD

- Protected in use to IP56 when lid is fully closed
- For OEMs (no back box supplied)
- RCDs can be either mechanically
 (passive) or electrically (active) latched
- Manufactured from glass nylon
- polymide for greater impact strength • Resistant to fertilisers, petrochemical
- products, mild acids and cleaning/washing agents



1 gang 13Amp 30mA RCD

code	description/size	pack
TM5625BK	mechanically latched	1
	109 x 75 x 90mm	
TM5626BK	electrically latched	1
	109 x 75 x 90mm	



1 gang 13Amp socket

code	description/size	pack
TM5627BK	109 x 75 x 90mm	1

Note:

Please note these products are only available in Black BK.

IP55 Enclosures protect against some ingress of dust and water and are ideal for use in the garden, garage and patio areas. IP55 rating:

5

Protected against dust limited ingress, not harmful deposit		Protected against low pressure jets of water from all direction, limited ingress permitted.
--	--	---

Product information

- · Lid allows security lock or seal to be fitted
- RCDs can be either electrically (active) or mechanically (passive) latched
- Underside cable entry prevents ingress of water
- Removable lid for easy wiring access
- Casing made from polycarbonate



IP55 Fused spur



2 gang 13Amp socket

with 30mA RCD (metal clad faceplate)		
code	description/size	pack
TM5501LG	mechanically latched	1
	166 x 142 x 90mm	
TM5508LG	electrically latched	1
	166 x 142 x 90mm	



Fused spur

with 30mA RCD		
code	description/size	pack
TM5502LG	mechanically latched	1
	166 x 142 x 90mm	



2 gang 13Amp socket

with 30mA RCD (polycarbonate faceplate		
code	description/size	pack
TM5510LG	mechanically latched	1
	166 x 142 x 90mm	



2 gang 13Amp socket

code	description/size	pack
TM5503LG	metal clad faceplate	1
	166 x 142 x 90mm	
TM5504LG	polycarbonate faceplate	1
	166 x 142 x 90mm	



TuffMaster

IP54 Sockets and switches | 223

The range of IP54 sockets and switches is splash proof and protected for limited dust ingress. These products are for use in areas such as residential porches, garages and covered patio areas and can also be used in selected industrial areas that will not be subjected to heavy jets of water. IP54 rating:



Sockets protected to IP54 when not in use and lid fully closed





1–way swi	tch		
code	description	size	pack
TM5404LG	2 gang	75 x 75 x 52mm	1



2-way switch

Intermediate switch

description

1 gang

2 gang

size

75 x 75 x 52mm

75 x 75 x 52mm

code

TM5403LG

TM5408LG

code	description	size	pack
TM5401LG	1 gang	75 x 75 x 52mm	1
TM5406LG	2 gang	75 x 75 x 52mm	1



Double pole switch

pack

code	description	size p	ack
TM5402LG	1 gang	75 x 75 x 52mm	1
TM5407LG	2 gang	75 x 152 x 52mm	1



1 gang switch with neon			
code	description	size	

code	description	size	pack
TM5409LG	2 way	75 x 75 x 52mm	1
TM5410LG	double pole	75 x 75 x 52mm	1



13Amp unswitched sockets

code	description	size	pack
TM5411LG	1 gang	75 x 75 x 62mm	1
TM5412LG	2 gang	75 x 152 x 62mm	1
TM5413LG	3 gang	75 x 229 x 62mm	1



13Amp switched socket

description size pack code TM5414LG 1 gang 75 x 152 x 62mm



13Amp switched sockets

k	code	description	size	pack
1	TM5416LG	2 gang	75 x 229 x 62	mm 1



13Amp switched socket double pole description size pack code TM5415LG 1 gang 75 x 152 x 62mm 1

Email sales@marshall-tufflex.com

www.marshall-tufflex.com

IP54 Unswitched sockets

TuffMaster

Switched sockets

Switches

Fused spurs

Product information

For interior perimeter fitting
Sockets are dual earth



• 1 and 2 gang switched sockets with or without neons

TuffMaster's metal clad range of switched sockets is

ideal for use in garages, offices and factories and other commercial and industrial environments.

• RCDs can be either electrically (active) or mechanically (passive) latched

 1 gang switched socket

 code
 size
 pack

 TM0001SG
 86 x 86 x 51mm
 10



 13Amp

 2 gang switched socket

 code
 size
 pack

 TM0002SG
 86 x 147 x 51mm
 5



 13Amp

 1 gang switched socket

 with neon

 code
 size
 pack

 TM0003SG
 86 x 86 x 51mm
 10



 13Amp

 2 gang switched socket

 with neon

 code
 size

 TM0004SG
 86 x 147 x 51mm



 10Amp

 1 gang 1-way switch

 code
 size
 pack

 TM0020SG
 80 x 80 x 48mm
 5



 10Amp

 2 gang 2-way switch

 code
 size
 pack

 TM0021SG
 80 x 80 x 48mm
 5



 20Amp switch

 double pole

 code
 size
 pack

 TM0026SG
 80 x 80 x 48mm
 5



 20Amp switch

 double pole with neon

 code
 size
 pack

 TM0027SG
 80 x 80 x 48mm
 5



 13Amp fused spur

 code
 size
 pack

 TM0022SG
 80 x 80 x 48mm
 5



2 gang 13Amp socket 30mA RCD code description/size pack TM0005SG mechanically latched 5 86 x 147 x 51mm TM0014SG electrically latched 5 86 x 147 x 51mm



 13Amp

 fused spur with neon

 code
 size
 pack

 TM0023SG
 80 x 80 x 48mm
 5



 Fused spur

 30mA RCD

 code
 description/size
 pack

 TM0007SG
 mechanically latched
 5

 86 x 86 x 51mm
 5



 13Amp fused spur double pole switch

 code
 size
 pack

 TM0024S6
 80 x 80 x 48mm
 5



2 gang unswitched socket faceplate 30mA RCD protected (polycarbonate)

code	description/size	раск
TM0010WH	mechanically latched	5
	86 x 147 x 15.6mm	



 13Amp fused spur double pole switch with neon

 code
 size
 pack

 TM0025SG
 80 x 80 x 48mm
 5



Fused spur faceplate 30mA RCD protected (polycarbonate)

code	description/size	pack
TM0009WH	mechanically latched	5
	86 x 86 x 15.6mm	

RCD sockets and spurs

Fax 01424 856611