

PCE

Connection
to the future

www.pcelectric.at • office@pcelectric.at



EVENT TECHNOLOGY
MIDNIGHT-SERIES

PC ELECTRIC GesmbH

...is specialized in the production of industrial plugs and sockets and distribution boxes. During the past few years, the company has gone through a phase of rapid development and is now one of the world's leading manufacturers of CEE plugs and sockets in the industry.

QUALITY

For maximum customer satisfaction and top performance (EN ISO 9001:2000 certification)

CUSTOMER FOCUS

- Partnership relationship
- Reliable operations
- Flexible operations
- Customized solutions
- Functional design

GLOBAL MARKET POSITION

- 80% exports
- Global network and alliances
- Fast communication system – short replying time

SPEED

Short delivery times due to flexible manufacturing

SCREWLESS CONNECTION TECHNOLOGY



1) Insert wire



2) Close terminal



3) Reopen terminal

- Time saving
- Screwless TT-terminal (PCE-patent in process)
- Open contact terminals, ready for assembly
- Fast cable installation
- Simple closing and opening just by thumb pressure

EVENT TECHNOLOGY

MIDNIGHT-SERIES

Visible plastic parts: black

Label: printed in the particular colour code



„Twist“ Plug

- with Twist cable-gland
- to order nickel-plated contacts please add a „v“ e.g. 013-6xv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
16	3	10	013-6x	
16	4	10		014-6x
16	5	10		015-6x
32	3	10	023-6x	
32	4	10		024-6x
32	5	10		025-6x



„Turbo Twist“ Plug

- screwless connection technology
- with Twist cable-gland
- to order nickel-plated contacts please add a „v“ e.g. 013-6TTxv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
16	3	10	013-6TTx	
16	4	10		014-6TTx
16	5	10		015-6TTx
32	3	10	023-6TTx	
32	4	10		024-6TTx
32	5	10		025-6TTx



„Power Twist“ Plug

- with Twist cable-gland
- nickel-plated contacts, with pilot contact

IP67 watertight

Amp	Poles	Pack. unit	230V	400V
63	3	2	033-6xs	
63	4	2		034-6xs
63	5	2		035-6xs
125	3	2	043-6xs	
125	4	2		044-6xs
125	5	2		045-6xs



Flanged plug straight

- according to EN 60309: For correct use a locking device has to be provided
- to order nickel-plated contacts please add a „v“ e.g. 613-6xv

IP44 splashproof

Amp	Pole	Pack. unit	230V	400V
Flange: 70x70mm, Fixing center: 56x56mm				
16	3	10	613-6x	
16	4	10		614-6x
16	5	10		615-6x
32	3	10	623-6x	
32	4	10		624-6x
32	5	10		625-6x



„Turbo Twist“

Flanged plug straight

- screwless connection technology
- according to EN 60309: For correct use a locking device has to be provided
- to order nickel-plated contacts please add a „v“ e.g. 613-6TTxv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
Flange: 70x70mm, Fixing center: 56x56mm				
16	3	10	613-6TTx	
16	4	10		614-6TTx
16	5	10		615-6TTx
32	3	10	623-6TTx	
32	4	10		624-6TTx
32	5	10		625-6TTx

EVENT TECHNOLOGY MIDNIGHT-SERIES



„Twist“ Connector

- with Twist cable-gland
- to order nickel-plated contacts please add a „v“ e.g. 213-6xv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
16	3	10	213-6x	
16	4	10		214-6x
16	5	10		215-6x
32	3	10	223-6x	
32	4	10		224-6x
32	5	10		225-6x



Turbo Twist“ Connector

- **screwless connection technology**
- with Twist cable-gland
- to order nickel-plated contacts please add a „v“ e.g. 213-6TTxv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
16	3	10	213-6TTx	
16	4	10		214-6TTx
16	5	10		215-6TTx
32	3	10	223-6TTx	
32	4	10		224-6TTx
32	5	10		225-6TTx



„Power Twist“ Connector

- with Twist cable-gland
- with lamellar contact
- nickel-plated contacts
- to order with pilot contact please add a „5“ e.g. 2335-6
- to order with pilot contact system (PCS) please add a „6“ e.g. 2336-6

IP67 watertight

Amp	Poles	Pack. unit	230V	400V
63	3	2	233-6xs	
63	4	2		234-6xs
63	5	2		235-6xs
125	3	2	243-6xs	
125	4	2		244-6xs
125	5	2		245-6xs



Flanged socket straight

- to order nickel-plated contacts please add a „v“ e.g. 313-6xv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
Flange: 70x70mm, Fixing center: 56x56mm				
16	3	10	313-6x	
16	4	10		314-6x
16	5	10		315-6x
32	3	10	323-6x	
32	4	10		324-6x
32	5	10		325-6x



Turbo Twist“ Flanged socket straight

- **screwless connection technology**
- to order nickel-plated contacts please add a „v“ e.g. 313-6TTxv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
Flange: 70x70mm, Fixing center: 56x56mm				
16	3	10	313-6TTx	
16	4	10		314-6TTx
16	5	10		315-6TTx
32	3	10	323-6TTx	
32	4	10		324-6TTx
32	5	10		325-6TTx

minimum order quantity: 50 pieces



„Power Twist“ Flanged socket straight

- with lamellar contact
- nickel-plated contacts
- to order with pilot contact please add a „5“ e.g. 3335-6xs
- to order with pilot contact system (PCS) please add a „6“ e.g. 3336-6xs

IP67 watertight

Amp	Poles	Pack. unit	230V	400V
-----	-------	------------	------	------

Flange: 100x100mm, Fixing center: 80x80mm

63	3	2	333-6xs	
63	4	2		334-6xs
63	5	2		335-6xs

Flange: 120x120mm, Fixing center: 100x100mm

125	3	2	343-6xs	
125	4	2		344-6xs
125	5	2		345-6xs



Flanged plug sloping

- to order nickel-plated contacts please add a „v“ e.g. 413-6xv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
-----	-------	------------	------	------

Flange: 85x70mm, Fixing center: 56x50mm

16	3	10	413-6x	
16	4	10		414-6x

Flange: 97x80mm, Fixing center: 73x60mm

16	5	10		415-6x
32	3	10	423-6x	
32	4	10		424-6x
32	5	10		425-6x



„Turbo Twist“ Flanged plug sloping

- **screwless connection technology**
- to order nickel-plated contacts please add a „v“ e.g. 413-6TTxv

IP44 splashproof

Amp	Poles	Pack. unit	230V	400V
-----	-------	------------	------	------

Flange: 85x70mm, Fixing center: 56x50mm

16	3	10	413-6TTx	
16	4	10		414-6TTx

Flange: 97x80mm, Fixing center: 73x60mm

16	5	10		415-6TTx
32	3	10	423-6TTx	
32	4	10		424-6TTx
32	5	10		425-6TTx



„Power Twist“ Flanged plug sloping

- with lamellar contact
- nickel-plated contacts
- to order with pilot contact please add a „5“ e.g. 4335-6xs
- to order with pilot contact system (PCS) please add a „6“ e.g. 4336-6xs

IP67 watertight

Amp	Poles	Pack. unit	230V	400V
-----	-------	------------	------	------

Flange: 112x100mm, Fixing center: 88x80mm

63	3	2	433-6xs	
63	4	2		434-6xs
63	5	2		435-6xs

Flange: 130x120mm, Fixing center: 108x100mm

125	3	2	443-6xs	
125	4	2		444-6xs
125	5	2		445-6xs

EVENT TECHNOLOGY MIDNIGHT-SERIES

PLUGS AND SOCKETS OUTLETS



Socket outlet (DIN 49440)

Austrian/German version

- screwed contact

IP54 splashproof

Amp	Poles	Pack. unit	250V
-----	-------	------------	------

Flange: 50x50mm, Fixing center: 38x38mm

16	3	100	1050-0s
----	---	-----	----------------



Socket outlet (DIN 49440)

Belgian/French version

- screwed contact
- with child-protection (shutter)

IP54 splashproof

Amp	Poles	Pack. unit	250V
-----	-------	------------	------

Flange: 50x50mm, Fixing center: 38x38mm

16	3	100	1040-0sc
----	---	-----	-----------------



Socket outlet

English version

- screwed contact
- side connection

IP54 splashproof

Amp	Poles	Pack. unit	250V
-----	-------	------------	------

Flange: 64x64mm, Fixing center: 52x52mm

13	3	100	1020-0s
----	---	-----	----------------

Flange: 50x50mm, Fixing center: 38x38mm

13	3	100	1020-5s
----	---	-----	----------------



Solid rubber plug

- with screwless cable gland
- dual-point earthing system
- insert: rubber

IP44 splashproof

Amp	Poles	Pack. unit	250V
16	2p+E	20	05622-ss



Solid rubber connector

Austrian/German standard

- with screwless cable gland
- insert: rubber

IP44 splashproof

Amp	Poles	Pack. unit	250V
16	2p+E	10	25621-ss
16	2p+E	10	25622-ss

with lid

with hinged lid

minimum order quantity: 100 pieces



Solid rubber connector

Belgian/French standard

- with screwless cable gland
- with lid
- insert: polyamide

IP44 splashproof

Amp	Poles	Pack. unit	250V
16	2p+E	10	24611-ss
16	2p+E	10	24612-ssc

with thick-bead

with thick-bead and child-protection



3-way connector solid rubber

Austrian/German standard

- with hinged lid
- insert: rubber

IP44 splashproof

Amp	Poles	Pack. unit	250V
16	2p+E	5	25322-sxs



3-way connector solid rubber

Belgian/French standard

- with lid
- insert: rubber

IP44 splashproof

Amp	Poles	Pack. unit	250V
16	2p+E	5	24311-sxs
16	2p+E	5	24311-sxsc

with child-protection

T-CONNECT



T-Connect

IP44 splashproof

Equipment	Cat.No.
1 CEE-plug 16A 3p 6h 1 CEE-socket 16A 3p 6h 1 cable entry (terminal block max. 3x2,5mm ²)	94325000



T-Connect

IP67 watertight

Equipment	Cat.No.
1 CEE-plug 16A 3p 6h 1 CEE-socket 16A 3p 6h 1 cable entry (terminal block max. 3x2,5mm ²)	94326000

EVENT TECHNOLOGY MIDNIGHT-SERIES



T-Connect with cable

IP44 splashproof
IP67 watertight

Equipment	Cat.No.
1,5m cable H07RN-F 3G1,5 with CEE-plug 16A 3p 6h	IP44: 94325001
1 cable entry (terminal block max. 3x2,5mm ²)	IP67: 94326001
1 CEE-socket 16A 3p 6h	



*T-Connect
2-way connector
with cable entry*

IP44 splashproof
IP67 watertight

Equipment	Cat.No.
1 cable entry (terminal block max. 3x2,5mm ²)	IP44: 94325002
2 CEE-sockets 16A 3p 6h outlet	IP67: 94326002



*T-Connect
2-way connector
with CEE-plug*

IP44 splashproof
IP67 watertight

Equipment	Cat.No.
1 CEE-plug 16A 3p 6h	IP44: 94325003
2 CEE-sockets 16A 3p 6h outlet	IP67: 94326003

COMPACT DISTRIBUTION BOXES – SERIES ST. ANTON



• plug and sockets are black

Entry	Outlet	Cat.No.
1 CEE-plug 16A 5p 400V	3 CEE-sockets 16A 5p 400V	9430052
1 CEE-plug 16A 5p 400V	1 CEE-socket 16A 5p 400V 2 sockets (DIN 49440) 16A 250V	9430053
1 CEE-plug 16A 5p 400V	3 CEE-sockets 16A 3p 230V	9430054

WALL- AND MOBILE DISTRIBUTION BOXES



Series Salzburg

dimensions: HxW = 370x298mm

- for wall-fastening
- solid rubber enclosure, with protective roof
- window up to max. 14 modules
- bottom of box and cover connected with joint
- ready wired for connection

IP44 splashproof

Equipment	Protection	Cat.No.
1 CEE-socket 32A 5p 400V black 1 CEE-socket 16A 5p 400V black 2 sockets (DIN 49440) 16A 250V black 1xM32 on top, 1xM32 from bottom	1 MCB 32A 3p-C 1 MCB 16A 3p-C 2 MCBs 16A 1p-B 1 RCD 40/4/0,03A over all outlets	92271649



Series Bruck

dimensions: HxW = 370x370mm

- for wall-fastening
- solid rubber enclosure, with protective roof
- window up to max. 18 modules
- bottom of box and cover connected with joint
- ready wired for connection

IP44 splashproof

Equipment	Protection	Cat.No.
1 CEE-socket 32A 5p 400V black 2 CEE-sockets 16A 5p 400V black 4 sockets (DIN49440) 16A 250V black 1xM32 on top, 1xM32 from bottom	1 MCB 32A 3p-C 2 MCBs 16A 3p-C 4 MCBs 16A 1p-B 1 RCD 63/4/0,03A over all outlets	92401543



Series Spitz

dimensions: HxWxD = 320x320x320mm

- portable, handy solid-rubber mobile box - stackable
- lifting hinged cover with 2 quick acting closures
- maximum safety – closed casing bottom with high ground clearance
- ready wired for connection

IP44 splashproof

Equipment	Protection	Cat.No.
2 CEE-sockets 32A 5p 400V black 2 CEE-sockets 16A 5p 400V black 4 sockets (DIN 49440) 16A 250V black 2m cable 5G6 with CEE-plug 32A 5p 400V black	unprotected 2 MCBs 16A 3p-C 4 MCBs 16A 1p-B 1 RCD 63/4/0,03A over all outlets	94741367

EVENT TECHNOLOGY

MIDNIGHT-SERIES



Series Steyr

dimensions: HxWxD = 72x430x115mm

- portable, handy solid-rubber mobile box
- housing with carrying handle
- ready wired for connection

IP44 splashproof

Equipment	Protection	Cat.No.
2 CEE-sockets 16A 5p 400V black 2 sockets (DIN 49440) 16A 250V black 2m cable 5G4 with CEE-plug 32A 5p 400V black	1 MCB 16A 3p-C 1 MCB 16A 1p-C	9440361



Series M-SVE3 63/11-12/V2/2M/A/MS

dimensions: HxWxD = 340x400x350mm

- shock-resistant, robust and mobile insulated thermoplastic box
- very lightweight and handy
- stackable
- resistant to weather and ageing

IP44 splashproof

Equipment	Protection	Cat.No.
1 CEE-socket 16A 5p 400V black 1 CEE-socket 32A 5p 400V black 12 sockets (DIN 49440) 16A 250V black Connection cable 44 kVA 2m cable 5G10 with CEE-plug 63A 5p 400V	1 MCB 16A 3p-C 1 MCB 32A 3p-C 12 MCBs 16A 1p-C 2 RCDs 63/0,03A	MZ853009286



Series M-SVE4 63/1-16/V17/G/E/A/MS

dimension: HxWxD = 340x560x350mm

- shock-resistant, robust and mobile insulated thermoplastic box
- very lightweight and handy
- stackable
- resistant to weather and ageing

IP44 splashproof

Equipment	Protection	Cat.No.
1 CEE-socket 16A 5p 400V black 16 sockets (DIN 49440) 16A 250V black Connection cable 44 kVA CEE-plug 63A 5p 400V with cable loop in the entry	1 MCB 16A 3p-C 16 RCD/MCB 16A 1p-C/0,03A 1 RCD 40/0,03A	MZ854009285

HINGED WINDOWS



Hinged windows IP67

- especially compact (robust) design, made of shock-resistant polycarbonate
- **for distributor's construction, O.E.M's, panel builders etc.**
- sprung-loaded window with integrated knurled screws
- size of hinged window suitable for 2, 4, 5, 6, 8, 10, 13, 18 modules
- with integrated gasket for flange mounting
- all metal parts corrosion-resistant

IP67 watertight

Mod.	Size		Cat.No.
2	49x93mm	40	900602s
4	85x93mm	20	900604s
5	103x93mm	20	900605s
6	121x93mm	15	900606s
8	157x93mm	15	900608s
10	193x93mm	15	900610s
13	247x93mm	10	900613s
18	337x93mm	12	900618s



Hinged windows IP54

- especially compact (robust) design, made of shock-resistant polycarbonate
- **for distributor's construction, O.E.M's, panel builders etc.**
- self-closing window
- size of hinged window suitable for 9, 10, 11, 12, 13, 14 and 18 modules
- angle of vee > 180°
- with integrated gasket for flange mounting
- integrated free position for lead seal

IP54 splashproof

Mod.	Size		Cat.No.
9	181x97mm	-	9006509s*
10	199x97mm	-	9006510s*
11	217x97mm	-	9006511s*
12	235x97mm	-	9006512s*
13	253x97mm	10	9006513s
14	271x97mm	10	9006514s
18	343x97mm	10	9006518s

* available in autumn 2009!



Группа ICS

Центр дистрибуции

Москва

+7 (495) 720-49-00, +7 (495) 720-49-08

ics@icsgroup.ru

www.icsgroup.ru

Санкт-Петербург

+7 (812) 337-10-87, +7 (812) 337-56-32

baltica@icsgroup.ru

www.icsbaltica.ru

Розничный магазин

Бакунинская, д.74, +7 (495) 720-49-05

www.icsmarket.ru

